

# Sustainable Viticulture Program

## Irrigation Management

*This section of the guidelines pertains to irrigated vineyards. If your vineyard is not irrigated, you may skip this section.*

Lowest Risk		Highest Risk			
	1	2	3	4	YOUR RANK
<b>Is there off site water movement?</b>	Irrigation practices result in no runoff. <i>AND</i> Conservation practices are in place to minimize runoff (i.e. perennial cover crops, subsoiling, buffer/filter strips, diversions, and grass waterways).	Irrigation practices result in no runoff. <i>AND</i> Conservation practices are present but some need improvement.	Irrigation practices result in no runoff but runoff and erosion occurs during high rainfall events. <i>AND/OR</i> Conservation practices need major improvement.	Runoff occurs when irrigating and/or during rainfall events.	
See also guidelines on drainage in Soil Management section.					
<b>What type of irrigation do you use?</b>	A low volume system such as drip is installed. <i>AND</i> System has been designed by a technician with experience in irrigation to ensure uniform distribution of water.	A low volume system such as drip is installed but no design was used.		A low volume system is not used.	

# Sustainable Viticulture Program

## Irrigation Management

<b>Irrigation System Maintenance</b>					
	<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>YOUR RANK</b>
<b>Do you check for distribution uniformity?</b>	System is checked at the beginning of each growing season by measuring emitter outflows and pressure differential in each zone.	Distribution uniformity is tested irregularly by measuring emitter outflows and pressure differential in each zone.		Distribution uniformity is never checked.	
<p>Drip irrigation distribution uniformity should be checked at the beginning of each growing season to ensure that the system is applying water in a uniform manner. This is particularly important for scheduling purposes and if fertigating.</p> <ol style="list-style-type: none"> <li>1. Using a graduated cylinder, measure the output of 3 consecutive emitters close to the pump, 3 in the middle of the zone and 3 at the farthest point from the pump.</li> <li>2. Convert the measured flow to gallons per hour as follows:  <math display="block">\frac{\text{__ mls}}{\text{__ sec}} \times 1 \text{ oz}/29.57 \text{ mls} \times 1 \text{ gal.}/128 \text{ fl.oz.} \times 60 \text{ sec.}/\text{min.} \times 60 \text{ min.}/\text{hr.}</math> </li> <li>3. Average the measurements, making sure the flow range does not exceed <math>\pm 15\%</math> of the average flow rate. Readings <math>&gt;15\%</math> indicate problems with the system, the most obvious being clogged emitters.</li> </ol>					

# Sustainable Viticulture Program

## Irrigation Management

<b>Irrigation System Maintenance</b>					
	1	2	3	4	YOUR RANK
<b>Is routine maintenance performed on the irrigation system?</b>	Water filters are inspected and cleaned whenever pressure differences indicate and irrigation lines are flushed at the beginning and end of each season. <i>AND</i> Chemical treatment of the water is completed if tests show a problem (e.g. to prevent precipitate buildup and kill algae or bacteria present in the system).	Water filters are inspected and cleaned whenever pressure differences indicate and irrigation lines are flushed at the beginning of the irrigation season each year.		Water filters are not regularly inspected and cleaned and irrigation lines are not flushed at all.	
OxiDate, a hydrogen dioxide product, is labeled as an irrigation disinfectant. Rutgers Cooperative Extension also has several useful publications on irrigation system maintenance - <a href="http://www.rce.rutgers.edu/">http://www.rce.rutgers.edu/</a> .					
<b>Is a flow meter installed?</b>	Flow meter is installed and used to monitor application rates throughout the season.	Flow meter is installed but not regularly used to monitor the system.	Flow meter is not installed.		

**Sustainable Viticulture Program  
Irrigation Management**

<b>Irrigation Scheduling</b>					
	<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>YOUR RANK</b>
<b>Is the vineyard's soil water holding capacity used in setting irrigation schedules?</b>	<p>The USDA Soil Survey is utilized to determine the average water holding capacity of the most common soils in the vineyard.</p> <p style="text-align: center;"><i>AND</i></p> <p>The effective rooting depth of your soils has been determined through excavation.</p> <p style="text-align: center;"><i>AND</i></p> <p>This information is used in irrigation scheduling.</p>	<p>The USDA Soil Survey is utilized to determine the average water holding capacity of the most common soils in the vineyard.</p> <p style="text-align: center;"><i>AND</i></p> <p>This information is used in irrigation scheduling.</p>		<p>Soil water holding capacity is not known. Vines are irrigated when soil looks dry.</p>	

## Sustainable Viticulture Program Irrigation Management

	1	2	3	4	YOUR RANK
<p><b>Are monitoring devices used to determine irrigation schedule?</b></p>	<p>Soil moisture monitoring devices (e.g. neutron gauge, tensiometer or gypsum blocks) are installed and used to track soil moisture depletion. <i>AND</i> Weather data is recorded and seasonal rainfall amounts are considered when deciding when to irrigate and how much water to apply.</p>	<p>Soil moisture monitoring is done by bucket auger [judging by feel]. <i>AND</i> Weather data is recorded and seasonal rainfall amounts are considered when deciding when to irrigate and how much water to apply.</p>	<p>Soil moisture monitoring devices are not installed. <i>BUT</i> Weather data is recorded and seasonal rainfall amounts are considered when deciding when to irrigate and how much water to apply.</p>	<p>An irrigation schedule is maintained regardless of soil moisture or weather conditions.</p>	
<p>Tensiometers reveal soil moisture potential in a specific area. They read changes in soil moisture by measuring the vacuum created by water movement through a ceramic tip. This mimics how soil moisture moves into the root zone of a plant. Tensiometers can help determine when to irrigate but not how much water should be applied. Begin irrigation when the tensiometer reads between 30 and 40 centibars. Observe the response on the tensiometer after irrigating. If it shows that the soil is wet (a gauge reading of 0-10), the system is working well. Operation times can be adjusted based upon the response of the tensiometer.</p> <p>There are a number of other methods for measuring soil moisture such as neutron probes and gypsum blocks. Alternatively, a more accurate method may be to measure vine water potential using pressure bombs.</p>					

**Sustainable Viticulture Program  
Irrigation Management**

	<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>YOUR RANK</b>
<b>What factors are used to determine length of time for irrigation?</b>	<p>Water is applied according to the water holding capacity of the soil, soil moisture measurement, vine demand and weather conditions at that time.</p> <p style="text-align: center;"><i>AND</i></p> <p>Application time is calculated according to the application rate of the system and the measured depletion in the root zone.</p>	<p>Water is applied according to the water holding capacity of the soil, vine demand and weather conditions at that time. Soil moisture is not measured.</p> <p style="text-align: center;"><i>AND</i></p> <p>Application time is calculated according to the application rate of the system.</p>	<p>Irrigation water is applied systematically when conditions are dry.</p>	<p>Irrigation water is applied systematically without regard to weather conditions, or water holding capacity of the soil.</p>	

## Sustainable Viticulture Program Irrigation Management

Vine water demand is highest as leaf area increases in spring and summer. Similarly, large canopies such as divided or minimally pruned canopies have higher water requirements than smaller canopies such as those in VSP training. According to Dr. Alan Lakso, a Concord vine with a full canopy needs about 4 – 4.5 gal/day in July and August. It is likely that vinifera vines with smaller canopies require less water.

Once the application rate of the system has been determined, (see previous sidebar) operating time can be determined. This is the length of time necessary to replace the water a single vine uses per day. Assuming a peak consumptive use for vinifera grapes is between 0.2 and 0.25 inches per day, calculation of irrigation time is possible by estimating the rooting area of the vine in square feet. For example: vines are planted 4' x 8', estimated rooting area is 32 sq.ft. and estimated peak consumptive use is 0.23 in/day.

$$0.23 \text{ in./day} / 12 \text{ in./ft.} \times 32 \text{ sq.ft.} \times 7.48 \text{ gal./cu.ft.} = 4.59 \text{ gal./vine/day}$$

$$\frac{4.59 \text{ gal./vine/day}}{\# \text{ emitters/vine} \times \text{gal./hr./emitter}} = \text{hrs. of operation}$$

To minimize leaching, do not exceed calculated operation time for peak consumptive use.

Peak consumptive use (PCU): Weather data was collected from a weather station located on a LI sod farm. The data was entered into an irrigation-scheduling model (Blaney Criddle Method) from Michigan State to calculate consumptive use for specific crops. PCU is the average daily amount of water consumed in evaporation from the soil and transpiration through the leaves in the photosynthetic process by a crop during the 6 – 10 days of the highest water consumption of the season. It generally occurs as the crop is nearing harvest, when vegetation is most abundant and temperatures are high.